


* For mounting on concrete + metallic plate, please contact us.

CLIPS	C max	Tightening torque (Nm)			Est'd weight
		Bolt or screw grade			
	mm	4.6	5.6	8.8	kg
41/035/AN	27	80	100	200	0,340
41/035/BN	34				0,350
Admissible side load (kN)		15	20	35	

N : nose height, not compressed, adapted to the rail type (see table overleaf).

SUB-PARTS




Full designation	
41/035/AN or 41/035/BN	
Components	
①	1x 41/035/R
②	1x 41/035/27/N or 41/035/34/N

All parts are hot dip galvanized.

For further anti-corrosion coating : see leaflet "Patented bolttable clips".

41/035
CLIP SELECTION FOR EACH RAIL

	F mm	K mm	H mm	Weight kg/m	Mounting	
					with	without
					pad	
A 45	125.0	45.0	55.0	22.10	41/035/BJ	41/035/AJ
A 55	150.0	55.0	65.0	31.80	41/035/BJ	41/035/AJ
A 65	175.0	65.0	75.0	43.10	41/035/BI	41/035/AI
A 75	200.0	75.0	85.0	56.20	41/035/BI	41/035/AI
Vign 30	106.0	56.0	125.5	29.98	41/035/BJ	41/035/AJ
Vign 36	115.0	58.2	128.0	36.54	41/035/BI	41/035/AI
Vign 46 (U 33)	134.0	62.0	145.0	46.36	41/035/BI	41/035/AI
S 30	108.0	60.3	108.0	30.03	41/035/BJ	41/035/AJ
S 33	105.0	58.0	134.0	33.47	41/035/BJ	41/035/AJ
S 34	117.5	61.9	117.5	34.72	41/035/BJ	41/035/AJ
S 41/10	125.0	67.0	138.0	41.38	41/035/BJ	41/035/AJ
S 49	125.0	67.0	149.0	49.43	41/035/BI	41/035/AI
GX 40	127.0	63.5	127.0	39.80	41/035/BI	41/035/AI
GX 42	131.8	65.1	131.8	42.16	41/035/BJ	41/035/AJ
BS 50 "O"	100.0	52.4	100.0	24.83	41/035/BJ	41/035/AJ
56 CR	171.0	76.0	101.5	56.81	41/035/BI	41/035/AI
JIS 30 (ASCE 60,S 30)	108.0	60.3	108.0	30.03	41/035/BJ	41/035/AJ
JIS 37	122.2	62.7	122.2	37.20	41/035/BI	41/035/AI
JIS 40 N	122.0	64.0	140.0	40.90	41/035/BJ	41/035/AJ
AS 22	93.7	50.8	93.7	22.90	41/035/BJ	41/035/AJ
AS 31	108.0	63.5	117.0	31.51	41/035/BJ	41/035/AJ
AS 41	127.0	63.5	137.0	40.72	41/035/BI	41/035/AI

For rail sections other than those listed on this page, please contact us.

We reserve the right to discontinue or change specifications or design at any time without prior notice and without incurring any obligation whatsoever.